



LUXAPOOL PRIMER / SEALER

(PART A – BASE COMPONENT)

MATERIAL SAFETY DATA SHEET

STATEMENT OF HAZARDOUS NATURE:

Hazardous according to criteria of Worksafe Australia

SECTION 1 - COMPANY AND MATERIAL SPECIFICATION

MANUFACTURERS NAME: MONOTEK Pty Ltd ABN 54 679 277 840

ADDRESS: (Head Office) 2/25 Jersey Road, Bayswater. Victoria. 3153

TELEPHONE No: (03) 9720 8777 **EMAIL:** admin@dpj.com.au

TRADE NAME: LUXAPOOL (PRIMER/SEALER) – PART A Component

USES: PROTECTIVE COATING PRIMER/ SEALER - BASE COMPONENT

SECTION 2 - INGREDIENTS

TECHNICAL NAME:	(CAS No.)	% BY WT.
AROMATIC EPOXY RESIN		30 - 60%
AROMATIC HYDROCARBON		30 - 60 %
GLYCOL ETHER		10-30%

SECTION 3 - PHYSICAL PROPERTIES

SPECIFIC GRAVITY (WATER =1): 0.950-1.050KG/LT **SOLUBILITY IN WATER:** INSOLUBLE

APPEARANCE AND ODOUR: WHITE OR PIGMENTED, VISCOUS LIQUID.

SECTION 4 - FLAMMABILITY & EXPLOSIVE PROPERTIES

FLASHPOINT: >30° C **METHOD:** Closed Cup (X) Open Cup ()

BOILING POINT/MELTING POINT : 137°C (B.P.)

EXTINGUISHING MEDIA: DRY CHEMICAL, CARBON DIOXIDE

SPECIAL FIRE FIGHTING REQUIREMENTS: BLANKET FLAMES WITH ONE OF THE ABOVE MEDIA

SECTION 5 - HEALTH HAZARD DATA

EFFECTS OF OVER EXPOSURE:

INGESTION OF LIQUID PAINT MAY BE HARMFUL DUE TO PRESENCE OF LIQUID HYDROCARBONS.

SPLASHES ENTERING THE EYES MAY CAUSE DISCOMFORT AND POSSIBLE DAMAGE.

PROLONGED SKIN CONTACT MAY HAVE A DE-FATTING EFFECT, POSSIBLY LEADING TO SKIN IRRITATION & / OR DERMATITIS.

VAPOUR: EXCESSIVE EXPOSURE TO HIGH VAPOUR CONCENTRATIONS MAY RESULT IN RESPIRATORY SYSTEM FAILURE. EXCESSIVE VAPOUR CONCENTRATIONS MAY PRODUCE ADVERSE EFFECTS UPON THE CENTRAL NERVOUS SYSTEM INCLUDING NAUSEA & DROWSINESS.

SWALLOWED: MAY CAUSE IRRITATION TO THE MOUTH, THROAT AND DIGESTIVE TRACT. LARGE DOSE MAY CAUSE DROWSINESS AND MAY LEAD TO UNCONCIOUSNESS.

EMERGENCY & FIRST AID PROCEDURES:

VAPOUR: PROVIDE FRESH AIR. IF BREATHING IS LABOURED. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. SEEK MEDICAL ADVICE.

CONTACT: REMOVE CONTAMINATED CLOTHING & WASH PRIOR TO RE-USING. WASH AFFECTED SKIN THOROUGHLY WITH SOAP AND WATER TO REMOVE PAINT.

FOR EYES - FLUSH IMMEDIATELY WITH WATER FOR 15 MINUTES AND SEEK MEDICAL ADVICE.

SWALLOWED: IF POISONING OCCURS, CONTACT DOCTOR OR POISONS INFORMATION CENTER. IF SWALLOWED **DO NOT** INDUCE VOMITING. GIVE A GLASS OF WATER TO DRINK. OBTAIN MEDICAL ADVICE IMMEDIATELY.

ADVICE TO DOCTOR: TREAT SYMPTOMATICALLY

LUXAPOOL PRIMER / SEALER

(PART A – BASE COMPONENT)

2

SECTION 6 - REACTIVITY DATA

STABILITY: Unstable () Stable (X)
CONDITIONS TO AVOID: OPEN FLAME, ARC OR SPARKS
HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE, CARBON DIOXIDE

SECTION 7 - STORAGE/TRANSPORT, SPILL & LEAKAGE CLEAN-UP PROCEDURE

STORAGE & TRANSPORT:

STORE IN A COOL, WELL VENTILATED AREA. STORE WELL AWAY FROM SOURCES OF HEAT OR IGNITION, ACIDS & OXIDISING AGENTS. KEEP CONTAINERS CLOSED AT ALL TIMES – CHECK REGULARLY FOR LEAKS. THIS MATERIAL IS CLASSIFIED AS DANGEROUS GOODS CLASS 3.2 UNDER THE AUSTRALIAN DANGEROUS GOODS CODE. TRANSPORT AS DIRECTED BY THE AUST. DANGEROUS GOODS CODE.

STEPS TO TAKE IN CASE MATERIAL RELEASED OR SPILLED:

VENTILATE AREA AND ELIMINATE ALL SOURCES OF IGNITION. USE ABSORBENT CLEAN UP MATERIALS. WEAR PERSONAL PROTECTION AS DESCRIBED ABOVE. TRANSFER TO SEALED CONTAINERS. DO NOT ALLOW FLOW INTO DRAINS OR WATER COURSES.

WASTE DISPOSAL PROCEDURES:

DISPOSE OF IN ACCREDITED WASTE DISPOSAL AREA IN ACCORDANCE WITH RELEVANT STATE & FEDERAL REGULATIONS.

SECTION 8 - SPECIAL PROTECTIVE EQUIPMENT

RESPIRATORY EQUIPMENT -

SPRAY APPLICATION: FILTER MASK IN CONFINED AREAS, TANKS OR AREAS OF POOR AIR CIRCULATION USE AIRLINE OR HOOD TYPE RESPIRATOR (QUALIFIED APPLICATORS ONLY)

BRUSH & ROLLER: NOT REQUIRED WITH GOOD VENTILATION.

VENTILATION REQUIREMENTS: LOCAL EXHAUST

PROTECTIVE GLOVES: NEOPRENE / RUBBER / PVC

EYE PROTECTION: GOGGLES

OTHER PROTECTIVE EQUIPMENT:

IN CONFINED AREAS, TANKS OR STAGNANT AIR CONDITIONS, USE EXPLOSION OR SPARK PROOF EQUIPMENT, INCLUDING NON SPARKING TOOLS AND SHOES.

SECTION 9 - SPECIAL PRECAUTIONS

HANDLING & STORAGE PRECAUTIONS:

KEEP CONTAINERS CLOSED. DON'T STORE NEAR HEAT OR OPEN FLAME

OTHER: AVOID PROLONGED BREATHING OF VAPOUR AND CONTACT WITH SKIN.

SECTION 10 - HAZARD CLASSIFICATION

U.N. NUMBER: 1263 **DANGEROUS GOODS CLASS:** 3.2 **SUBSIDIARY RISK:** N/A
HAZCHEM CODE: 3 (Y) **POISONS SCHEDULE:** 5 **GROUP TEXT EPG:** 3C1
PACKAGING GROUP: III



DPJ COATINGS SYSTEMS

A Division of MONOTEK Pty Ltd ABN 54 679 277 840

Victoria: (Head Office)
2 / 25 Jersey Road, Bayswater. 3153

Ph: (03) 9720 8777
E: sales@poolpaintonline.com.au

www.poolpaintonline.com.au

Product Name: LUXAPOOL® Primer Base / Part A
Page 2 of 2

Issued: 12/08/2024

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since MONOTEK Pty Ltd cannot anticipate all the conditions and situations under which the product may be used, each user must, prior to use, assess and control the risks arising from the use of the product.