



LUXAPOOL® POOLSIDE & PAVING

MATERIAL SAFETY DATA SHEET

STATEMENT OF HAZARDOUS NATURE: *Not classified as Hazardous.*

SECTION 1 - COMPANY AND MATERIAL SPECIFICATION

MANUFACTURER / AGENTS NAME:

D.P.J. Coating Systems Pty Ltd. ACN 005 509 679 ABN 56 005 509 679

ADDRESS: (Head Office) 2 / 25 Jersey Road, Bayswater. Victoria 3153

TELEPHONE No: (03) 9720 8777 / Free Call -1800 062 301 **FACSIMILE:** (03) 9720 8540

TRADE NAME: LUXAPOOL POOLSIDE & PAVING

USES: SURFACE COATING – Waterbased, flexible anti-slip coating.

SECTION 2 - INGREDIENTS

TECHNICAL NAME:	(CAS No.)	% BY WT.
Water and minor components	N/A	30 - 60%
Titanium dioxide	13463-67-7	10 - 30 %
Pigments		10 - 30%
Acrylic copolymer		10 – 30%
Propylene Glycol	57-55-6	< 1%
White Spirit	64742-88-7	<1%

SECTION 3 - PHYSICAL PROPERTIES

SPECIFIC GRAVITY (WATER =1): Approx. 1.2 - 1.4 (20°C) **SOLUBILITY IN WATER:** Miscible

BOILING POINT: Approx. 100°C (water)

APPEARANCE AND ODOUR: OPAQUE VISCOUS, COLOURED LIQUID, MILD ODOUR

SECTION 4 - FLAMMABILITY & EXPLOSIVE PROPERTIES

FLASHPOINT: N/A **METHOD:** Closed Cup (X) Open Cup ()

EXTINGUISHING MEDIA: Use extinguishing media suited to the primary source of the fire.

SPECIAL FIRE FIGHTING REQUIREMENTS: Not flammable, however after evaporation of the aqueous component residual material may decompose evolving toxic fumes and gases

SECTION 5 - HEALTH HAZARD DATA

Inhalation Not usually an inhalation risk.

Ingestion Rinse mouth thoroughly with water and give water to drink. DO NOT induce vomiting. Contact a doctor or call Poisons Information (Aust. 13 11 26).

Skin Wash with soap and water and rinse thoroughly. Remove contaminated clothing and wash before re-use. Seek medical advice if effects persist.

Eye Contact Irrigate with copious quantity of water for at least 15 minutes with eyelids held open. We recommend seeking medical advice in all cases of eye exposure.

Advice to Doctor Treat symptomatically.

Protection for First Aiders Avoid risking your own health and that of others through adherence to safe procedures in all treatment situations. Use of protective equipment such as latex gloves and mouth protection is recommended.

SECTION 6 - REACTIVITY DATA

STABILITY: Unstable () Stable (X)

HAZARDOUS POLYMERIZATION: Will Not Occur

SECTION 7 - ECOLOGICAL DATA

Persistence and Degradability Components other than pigments/fillers: Can be virtually eliminated from water by abiotic processes e.g. adsorption onto activated sludge. Pigment/Filler components: Persistent and do not biodegrade. No evidence of mobility of these components.

Bioaccumulative Significant accumulation in organisms is not to be expected.

Potential Basis for Assessment This statement derived from properties of the individual components and products of similar composition.

Acute Toxicity – Fish LC50 (Leuciscus idus, 96 hr): >100 mg/l

The product has not been tested. The statement has been derived from data on the individual components.

Acute Toxicity – Bacteria EC50 (96h) >100 mg/l (DEV: L2)

Inhibition of degradation activity in activated sludge is not to be anticipated during introduction of low concentrations.

Other Information The product contains no organically bound halogen (AOX)

SECTION 8 - STORAGE/TRANSPORT, SPILL & LEAKAGE CLEAN-UP PROCEDURE

STORAGE & TRANSPORT:

STORE IN A COOL, WELL VENTILATED AREA AWAY FROM HEAT SOURCES. CONTAINERS SHOULD BE ALWAYS KEPT CLOSED IN STORAGE AND PROPERLY LABELLED. STORE ONLY IN ORIGINAL AND APPROVED CONTAINERS.

STEPS TO TAKE IN CASE MATERIAL RELEASED OR SPILLED:

USE ABSORBENT CLEAN UP MATERIALS

WASTE DISPOSAL PROCEDURES:

IN SEPARATE CLOSED METAL CONTAINERS IN ACCORDANCE WITH LOCAL REGULATIONS.

SECTION 9 - SPECIAL PROTECTIVE EQUIPMENT

RESPIRATORY EQUIPMENT: N/A

SPRAY APPLICATION: N/A

BRUSH & ROLLER: NOT REQUIRED with good ventilation.

VENTILATION REQUIREMENTS: LOCAL EXHAUST

PROTECTIVE GLOVES: NEOPRENE / RUBBER / PVC

EYE PROTECTION: GOGGLES

SECTION 10 - SPECIAL PRECAUTIONS

HANDLING & STORAGE PRECAUTIONS:

KEEP CONTAINERS CLOSED. DON'T STORE NEAR HEAT OR OPEN FLAME

SECTION 11 - HAZARD CLASSIFICATION

U.N. NUMBER: N/A

DANGEROUS GOODS CLASS: N/A

SUBSIDIARY RISK: N/A

HAZCHEM CODE: N/A

POISONS SCHEDULE: N/A

GROUP TEXT EPG: N/A

D P J COATING SYSTEMS Pty Ltd

ABN 56 005 509 679

ACN 005 509 679

Victoria: (Head Office) 2 / 25 Jersey Road, Bayswater. 3153
NSW: 16/122-124 Hassall Street, Wetherill Park. 2164

Phone: (03) 9720 8777 Facsimile: (03) 9720 8540

Toll free - 1800 062 301 (Australia-wide)

Email: sales@poolpaintonline.com.au

w w w . p o o l p a i n t o n l i n e . c o m . a u

Product Name: LUXAPOL® Poolside & Paving

Issued: 01/12/2016

Page 2 of 2

This MSDS summarises, to our best knowledge at the date of issue, the health and safety hazards of the product and provides general guidance on how to safely handle it in the workplace. Since D.P.J. Coating Systems Pty Ltd cannot anticipate all the conditions and situations under which the product may be used, each user must, prior to use, assess and control the risks arising from the use of the product.