



LUXAPOOL® SUPA-SEAL PRIMER

MATERIAL SAFETY DATA SHEET

STATEMENT OF HAZARDOUS NATURE:

Hazardous according to criteria of Worksafe Australia

SECTION 1 - COMPANY AND MATERIAL SPECIFICATION

MANUFACTURER / AGENTS NAME:

D.P.J. Coating Systems Pty Ltd. ACN 005 509 679 ABN 56 005 509 679

ADDRESS: (Head Office) 2 / 25 Jersey Road, Bayswater. Victoria 3153

TELEPHONE No: (03) 9720 8777 / Free Call -1800 062 301 **FACSIMILE:** (03) 9720 8540

TRADE NAME: SUPER SEAL PRIMER **USES:** SURFACE COATING / SEALER & PRIMER

SECTION 2 - INGREDIENTS

TECHNICAL NAME:	(CAS No.)	% BY WT.
Xylene (mixed isomers)	1330-20-7	60-100 %
Solvent naphtha (petroleum) light Aromatic	64742-95-6	10-30 %
Acrylic copolymer		10-30 %
Ethanol	64-17-5	1-10 %

SECTION 3 - PHYSICAL PROPERTIES

SPECIFIC GRAVITY (WATER =1): Approx. 0.87 @ 15 Deg C.

SOLUBILITY IN WATER: Negligible.

BOILING POINT: 136 - 145 C. Approximately

APPEARANCE AND ODOUR: Clear, colourless liquid. Aromatic Odour

SECTION 4 - FLAMMABILITY & EXPLOSIVE PROPERTIES

FLASHPOINT: Approx 28 C. (ASTM D-56) **METHOD:** Closed Cup (X) Open Cup ()

EXTINGUISHING MEDIA: Extinguish fire with the following: alcohol resistant foam , foam, dry chemical powder or carbon dioxide.

SPECIAL FIRE FIGHTING REQUIREMENTS: Use water to cool fire-exposed containers. If a leak or spill has not ignited, use water spray to disperse the vapours and to protect personnel attempting to stop leak. Water spray may be used to flush spills away from exposures. Prevent runoff from fire control or dilution from entering waterways, sewers or drinking water supply.

SECTION 5 - HEALTH HAZARD DATA

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer artificial respiration if breathing is stopped. Keep at rest. Seek medical attention.

Ingestion DO NOT induce vomiting. Immediately contact a doctor or call Poisons Information (Aust. 13 11 26).

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Wash contact areas with soap and water. Launder contaminated clothing before re-use.

Eye Contact If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Seek medical attention.

Advice to Doctor Treat symptomatically. Note: Potential for chemical pneumonitis.

LUXAPOOL® SUPA-SEAL PRIMER

SECTION 6 - REACTIVITY DATA

STABILITY: Unstable () Stable (X)

CONDITIONS TO AVOID: Heat, sparks, flame and build up of static electricity.

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE,

SECTION 7 - STORAGE/TRANSPORT, SPILL & LEAKAGE CLEAN-UP PROCEDURE

STORAGE & TRANSPORT:

Avoid contact with skin and inhalation of vapours. Use in well ventilated area away from all ignition sources. Avoid sparking conditions. Ground and bond all transfer equipment.

Drums must be grounded and bonded. Outside or detached storage preferred.

Store in a cool area away from all ignition sources.

CONTAINERS SHOULD BE ALWAYS KEPT CLOSED IN STORAGE AND PROPERLY LABELLED.

STORE ONLY IN ORIGINAL AND APPROVED CONTAINERS.

STEPS TO TAKE IN CASE MATERIAL RELEASED OR SPILLED:

Eliminate all sources of ignition. Remove leaking containers to detached area.

Wear protective equipment to prevent skin and eye contamination and inhalation of vapours.

Contain - prevent contamination of drains and waterways. Use absorbent (soil, sand, vermiculite).

WASTE DISPOSAL PROCEDURES:

Collect and seal in properly labelled drums for disposal. Wash area with excess water

SECTION 8 - SPECIAL PROTECTIVE EQUIPMENT

RESPIRATORY EQUIPMENT -

SPRAY APPLICATION: FILTER MASK

IN CONFINED AREAS, TANKS OR AREAS OF POOR AIR CIRCULATION USE AIRLINE OR HOOD TYPE RESPIRATOR (Qualified & Trained personnel ONLY)

BRUSH & ROLLER: NOT REQUIRED with good ventilation.

VENTILATION REQUIREMENTS: LOCAL EXHAUST

PROTECTIVE GLOVES: NEOPRENE / RUBBER / PVC

EYE PROTECTION: GOGGLES

OTHER PROTECTIVE EQUIPMENT:

IN CONFINED AREAS, TANKS OR STAGNANT AIR CONDITIONS, USE EXPLOSION OR SPARK PROOF EQUIPMENT, INCLUDING NON SPARKING TOOLS AND SHOES.

SECTION 9 - SPECIAL PRECAUTIONS

HANDLING & STORAGE PRECAUTIONS:

KEEP CONTAINERS CLOSED. DON'T STORE NEAR HEAT OR OPEN FLAME

OTHER: AVOID PROLONGED BREATHING OF VAPOUR AND CONTACT WITH SKIN.

SECTION 10 - HAZARD CLASSIFICATION

U.N. NUMBER: 1263

DANGEROUS GOODS CLASS: 3.2

SUBSIDIARY RISK: N/A

HAZCHEM CODE: 3 (Y)

POISONS SCHEDULE: S6

GROUP TEXT EPG: 3C1

PACKAGING GROUP: III



DPJ COATINGS SYSTEMS Pty Ltd

ABN 56 005 509 679

ACN 005 509 679

Victoria: (Head Office) 2 / 25 Jersey Road, Bayswater. 3153
NSW: 16/122-124 Hassall Street, Wetherill Park. 2164

Phone: (03) 9720 8777 Facsimile: (03) 9720 8540

Toll free - 1800 062 301 (Australia-wide)

Email: sales@poolpaintonline.com.au

w w w . p o o l p a i n t o n l i n e . c o m . a u